

Windload Charts | TC970 Series

B = 20 P.S.F. (958 Pa)


D = 30 P.S.F. (1436 Pa) $E = 40 \text{ P.S.F.} (1915 \text{ Pa})^{-1} \text{ Scale: N.T.S.}$

Function: Window Wall Detail: Design Criteria


SHEET 1 OF 1

Description: 2 1/4" X 9" Offset Glazed For 1" Glass


C = 25 P.S.F. (1197 Pa)



I = 13.850 IN⁴ $S = 3.957 IN^3$



24 MULLION HEIGHT IN FEET 23 22 21 20 19 18 17 16 15 MULLION SPACING IN FEET I = 29.032 IN 4




TH926 WITH STEEL REINFORCEMENT 1 1/2" X 6" X 10 GA.


- Mullions are assumed to be single span, simple beam elements, uniformly loaded and adequately braced to prevent lateral-torsional buckling. All other complex design conditions shall be reviewed by Arcadia or a design professional.
- Aluminum extrusions shall be 6063-T6 alloy. Allowable stresses to be derived per Aluminum Design Manual. Deflection limitation of mullions shall be in accordance with AAMA TIR-A11 of L/175 for spans up to 13'-6" and L/240 + 1/4" for all others where L is equal to the span of mullion.
- A design professional shall be consulted to confirm that no lite of glass deflects more than H/175 or 3/4", whichever is less, where H indicates the height of glass

TH926


- For mullions containing steel reinforcement, the reinforcement is assumed to be installed for the full length of the mullion. A design professional shall be consulted for instances where steel reinforcement is installed for a partial length of the mullion span.
- Windload pressure determinations shall be per ASCE 7 and according to local governing codes. A professional engineer shall be consulted for the most current laws and local building codes.
- Selection of perimeter fasteners and attachment of glazing system to building structure are project specific and therefore shall be reviewed and determined by a design professional
- Arcadia assumes no responsibility for selecting the appropriate systems for specific projects.



I = 14.601 IN $S_1 = 2.344 \text{ IN}^3$ $S_{s} = 1.920 \text{ IN}^{3}$



TH958 / TH959



MULLION SPACING IN FEET

I = 23.423 IN

 $S = 5.108 \text{ IN}^3$

TH944




Deadload Charts | TC970 Series

Description: 2 1/4" X 9" Offset Glazed for 1" Glass

Function: Window Wall Detail: Design Criteria

Deadload Charts for 1" Glass (7.00 PSF) | Scale: N.T.S.

SHEET 1 OF 1



CURVE REPRESENTATION

A (----) = 1/8" PTS.

B (——) = 1/4" PTS.