



Doors
Arcadia Inc.

Final Assembly: Multiple Locations in the USA
Life Expectancy: 60 Year(s)
End of Life Options: Salvageable/Reusable in its Entirety,
Recyclable (96%), Landfill (4%)

Ingredients:

Glass: Fumed Silica; **Aluminum:** UNS A96063 Aluminum Alloy;
Santoprene: Cutting Oils; Polypropylene; Siloxanes and
Silicones, di-Me; Kaolin, calcined; Zinc oxide; Octadecanoic acid,
calcium salt; **Stainless Steel Spacer:** Steel manufacture,
chemicals; **Silicone:** Siloxanes and Silicones, di-Me; Silica,
amorphous, fumed, cryst.-free; **Distillates (petroleum),
hydrotreated middle;** Silanetriol, ethyl-, triacetate; **Stainless
Steel:** Steel manufacture, chemicals; **Hot Metl Butyl:** Talc;
Sealant: 1-Propene, 2-methyl-, homopolymer; **Argon Gas (Gas
Infill):** Argon

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable
I-14 Responsible Sourcing: Not Applicable

ARD-0002
EXP. 01 MAR 2027
Original Issue Date: 2021